




Project Statement

Cinder Lake Landfill requires a plan for landfill mining and excavation to achieve the design for future Cell D.


How will this be achieved?

Create more space for future waste by re-sequencing Cell D that will include a portion of Cell C & the South Thumb





Cen C & me Soum Inumo





Site Background

Cinder Lake Landfill

- 343-acre municipal solid waste landfill
- Located in East Flagstaff, AZ
- Services a 70-mile radius around Flagstaff




Current Conditions

Involved cells

*Cell D : Basalt rock

*Cell C : Construction debris

*South Thumb: Municipal Solid Waste (MSW)







Site Background

Cinder Lake Landfill

- 343-acre municipal solid waste landfill
- Located in East Flagstaff, AZ
- Services a 70-mile radius around Flagstaff




Current Conditions

Involved cells


*Cell D : Basalt rock

*Cell C : Construction debris

*South Thumb: Municipal Solid Waste (MSW)











Landfill Mining & Excavation Plan


Project Schematics








Project Schematics






Current


Cell C & ST Excavated



Cell C Excavated




Final




Provided by Matt Morales, City of Flagstaff

Cell Volumes

What are the design volumes?







Project Duration & Processing Rate

How many cubic yards per day will need to be excavated $\ensuremath{\mathcal{E}}$ mined, and for how many days?

	Cell D	Cell C	South Thumb	
Volume (cu.yd/day)	1,600,000 soil expansion 2,080,000	730,000	207,000	
Duration (months)	39	16	5	
Daily Rate (cu.yd/day)	1,900	2,100	1,900	

Overall

2,300 cu.yd/day 60 months



Equipment

What equipment will be needed to perform the excavation & mining?

Excavator

Loader

Vibratory Screener



Truck

Dozer

Trommel







ScreenMachine

Backhoe




Cat Equipment


Mass Balance

Now that everything has been excavated, where is it all going?


Mass Balance Cell C



Mass Balance South Thumb




Mass Balance Cell D






Mass Balance Cell C






Mass Balance South Thumb






Mass Balance Cell D





Segregation Areas

How will the excavated material be segregated?



Rock Segregation Area 30 acres Rip Rap 1 Cover 1 Landscaping 1 Landscaping 3 Landscaping 5 Landscaping 7 Rip Rap 2 Cover 2 Landscaping 2 Landscaping 4 Landscaping 6 Landscaping 6




Waste Segregation Area

2.2 acres

T = Trommel

V = Vibratory Screener





Rock Segregation Area

30 acres

Rip-Rap 1	Cover 1	Landscaping 1	Landscaping 3	Landscaping 5	Landscaping 7	
Rip-Rap 2	Cover 2	Landscaping 2	Landscaping 4	Landscaping 6	Landscaping 8	



Environmental Controls

Air Quality

Dust Controls

- · Water spraying (3 water trucks)
- · 3000 gallons of reclaimed water every 25 minutes

Dust Monitoring

· Digital Opacity Compliance System (DOCSII)





Hazardous Waste

If encountered, must be handled and managed properly

Identification color, smell, containers full of liquid



Testing ignitability, corrosivity, reactivity, toxicity




Storing no more than 90 days on site



TSD Facilities

Treatment, storage or disposal (TSD) facility in Coolidge, AZ



Stormwater Management

Waste Segregation Area

- · Asphalt platform
- · Silt fence barrier

Retention Basin Segregation Area Silt FenceBarrier

Retention Basin

· Polyethylene lined retention basin

Water Monitoring

- · Test against Clean Water Act
- · Transport to wastewater treatment plant





Air Quality

Dust Controls

- Water spraying (3 water trucks)
- 3000 gallons of reclaimed water every 25 minutes

Dust Monitoring

Digital Opacity Compliance System (DOCSII)



Virtual Technology, LLC (DOCSII 2013)

Air Monitoring

Gases — Hydrogen Sulfide
 Carbon Monoxide
 Methane

• GEM2000 & MiniRAE3000












Stormwater Management

Waste Segregation Area

- Asphalt platform
- Silt fence barrier



Retention Basin

Polyethylene lined retention basin

Water Monitoring

- Test against Clean Water Act
- Transport to wastewater treatment plant



Hazardous Waste

If encountered, must be handled and managed properly

Identification

color, smell, containers full of liquid



Testing

ignitability, corrosivity, reactivity, toxicity



Storing

no more than 90 days on site



TSD Facilities

Treatment, storage or disposal (TSD) facility in Coolidge, AZ



Cost of Implementation

Cycle Hauling = \$5,580,000
Excavation = \$5,800,000
Waste Segregation Area = \$716,000
Air Quality & Dust Control = \$407,000
Hazardous Waste = \$14,000



Total Cost = \$12,520,000



Impacts

Economic benefits

- Extension of closure date
- Recovery of landfill cover
- Recovery of sellable materials



Environmental

• Minimizing the use of resources



Acknowledgments

Clients - Matt Morales, P.E.
Brian Bluelake, P.E.

Technical Advisors - Dr. Bridget Bero, P.E.

Dr. Thomas Rogers, P.E.





Questions?





