
# SRP EVAP

#### **ME 476C Spring 2025**

Samantha Synk – Project Manager
Lilliana Hadik-Barkoczy-Logistics Manager
Garet Bowels-Manufacturing Engineer
Trey Bushling-CAD Engineer
Jorge Cesin-Financial Manager
Brendan Steele-Test Engineer



# **CAD & Schematics**







Figure 1: CAD View 1

Figure 2: CAD View 2

# **CAD & Schematics**



# **Updated Design Efforts & Engineering Calculations**

We are creating conditions for turbulent free convection to mimic the average conditions at the Grand Canal in April 2025.

Weather data from SRP gave us the parameters needed to characterize the buoyant forces and viscous forces which drive evaporation under free convective conditions.

Final design parameters to achieve this Grashof number:

$$Gr_m = 7.179 \times 10^{11}$$

After dimensionless scaling, closest Grashof number we can reproduce in the apparatus:

$$Gr_m = 1.226 imes 10^{11}$$

Final design parameters to achieve this Grashof number:

$$T_{\infty}=45^{\circ}\mathrm{F}$$

$$T_s=90^\circ {
m F}$$

$$\phi=2\%$$

$$L_c=10ft$$

### **MATLAB Code**

```
Exact matches (top 15):
%% ------ TARGET -----
                                                                                                L(ft)
                                                                                                        L(m) T inf(F)
                                                                                                                        T s(F)
                                                                                                                                 RH (%)
                                                                                                                                        Gr (signed)
                                                                                                                                                                            Stability
                                  % Canal average @ 2 m above water (from SRP Grand Canal data)
                                                                                                                                                        |err|%
                                                                                                                                                                   ∆rho air
Gr target canal = 7.751e11:
                                                                                                10.00
                                                                                                       3.048
                                                                                                                 53.0
                                                                                                                          49.0
                                                                                                                                  68.0
                                                                                                                                         -8.507e+09
                                                                                                                                                         0.01
                                                                                                                                                               -8.112e-03
                                                                                                                                                                               STABLE
band pct
               = 0.50:
                                  % ±50% tolerance band for matches
                                                                                                10.00
                                                                                                      3.048
                                                                                                                          82.0
                                                                                                                                  58.0
                                                                                                                                         -8.505e+09
                                                                                                                                                         0.01
                                                                                                                                                               -9.671e-03
                                                                                                                                                                               STABLE
require_same_stability = true;
                                  % Requires the same Δrho_air sign as canal
                                                                                                                 89.0
stability eps = 1e-9;
                                  % Anything with | Δrho air | < eps is treated as "neutral"
                                                                                                10.00
                                                                                                       3.048
                                                                                                                 57.0
                                                                                                                          53.0
                                                                                                                                  75.0
                                                                                                                                         -8.507e+09
                                                                                                                                                         0.01
                                                                                                                                                               -8.284e-03
                                                                                                                                                                               STABLE
                                                                                                10.00
                                                                                                      3.048
                                                                                                                 78.0
                                                                                                                          72.0
                                                                                                                                  58.0
                                                                                                                                         -8.507e+09
                                                                                                                                                         0.02
                                                                                                                                                               -9.171e-03
                                                                                                                                                                               STABLE
% OPTIONAL: scale target by (L/L ref)^3 to account for shorter apparatus
                                                                                                10.00
                                                                                                       3.048
                                                                                                                 52.0
                                                                                                                          48.0
                                                                                                                                  66.0
                                                                                                                                         -8.508e+09
                                                                                                                                                         0.02
                                                                                                                                                               -8.071e-03
                                                                                                                                                                               STABLE
scale target by L3 = true;
                                  % <<< set true to preserve regime with short L
                                                                                                                                         -8.503e+09
                                                                                                                                                               -8.919e-03
                                                                                                10.00
                                                                                                       3.048
                                                                                                                 72.0
                                                                                                                          67.0
                                                                                                                                  69.0
                                                                                                                                                         0.03
                                                                                                                                                                               STABLE
L ref canal m
                 = 13.716;
                                  % [m] canal characteristic length used in doc
                                                                                                                                                               -9.151e-03
                                                                                                10.00
                                                                                                      3.048
                                                                                                                 79.0
                                                                                                                          71.0
                                                                                                                                         -8.508e+09
                                                                                                                                                         0.03
                                                                                                                                                                               STABLE
                                                                                                                                  25.0
                                                                                                10.00
                                                                                                       3.048
                                                                                                                 66.0
                                                                                                                          59.0
                                                                                                                                         -8.510e+09
                                                                                                                                                         0.05
                                                                                                                                                               -8.588e-03
                                                                                                                                                                               STABLE
%% ------ RANGES ------
                                                                                                                                         -8.502e+09
                                                                                                                                                               -9.654e-03
                                                                                                10.00
                                                                                                       3.048
                                                                                                                 88.0
                                                                                                                          82.0
                                                                                                                                  70.0
                                                                                                                                                         0.05
                                                                                                                                                                               STABLE
% Length (feet → meters)
                                                                                                10.00
                                                                                                      3.048
                                                                                                                 59.0
                                                                                                                          54.0
                                                                                                                                  45.0
                                                                                                                                         -8.502e+09
                                                                                                                                                         0.05
                                                                                                                                                               -8.335e-03
                                                                                                                                                                               STABLE
                            % Apparatus length in feet
L_ft = 10;
                                                                                                10.00
                                                                                                       3.048
                                                                                                                 76.0
                                                                                                                          69.0
                                                                                                                                  36.0
                                                                                                                                         -8.510e+09
                                                                                                                                                         0.05
                                                                                                                                                               -9.046e-03
                                                                                                                                                                               STABLE
                               % Convert to meters
L m = L ft * 0.3048;
                                                                                                                                                              -8.465e-03
                                                                                                10.00
                                                                                                      3.048
                                                                                                                 62.0
                                                                                                                          57.0
                                                                                                                                  52.0
                                                                                                                                         -8.501e+09
                                                                                                                                                         0.06
                                                                                                                                                                               STABLE
                                                                                                10.00 3.048
                                                                                                                 86.0
                                                                                                                          80.0
                                                                                                                                         -8.501e+09
                                                                                                                                                               -9.552e-03
                                                                                                                                                                               STABLE
                                                                                                                                  68.0
                                                                                                                                                         0.06
% Temperatures (°F → K)
                                                                                                                                                               -9.515e-03
                                                                                                10.00
                                                                                                       3.048
                                                                                                                 85.0
                                                                                                                          79.0
                                                                                                                                  67.0
                                                                                                                                         -8.511e+09
                                                                                                                                                         0.06
                                                                                                                                                                               STABLE
Tinf F = 45:1:90;
                                  % Ambient air temperature (°F)
                                                                                                10.00
                                                                                                      3.048
                                                                                                                 85.0
                                                                                                                          77.0
                                                                                                                                  38.0
                                                                                                                                         -8.500e+09
                                                                                                                                                         0.07
                                                                                                                                                               -9.430e-03
                                                                                                                                                                               STABLE
Ts F = 45:1:90;
                                  % Water surface temperature (°F)
      = @(F) (F - 32) * 5/9 + 273.15;
                                                                                               Best achievable by length (max |Gr|; tie→closest % to target):
% Relative humidity
                                                                                                                                 RH (%)
                                                                                                                                                                   Arho air Stability
                                                                                                        L(m) T inf(F)
                                                                                                                        T s(F)
                                                                                                                                                |Gr|
                                                                                                                                                        |err|%
RH_{vec} = (2:1:80)/100;
                                  % 2-80% → 0.02-0.80
                                                                                                10.00
                                                                                                       3.048
                                                                                                                 45.0
                                                                                                                          90.0
                                                                                                                                   2.0
                                                                                                                                          1.212e+11 1325.00
                                                                                                                                                                 1.191e-01
                                                                                                                                                                             UNSTABLE
```

Figure 3: MATLAB Code Based on Calculated Grashof Number

Figure 4: Output of MATLAB Code

### Bill of Materials

Link to BOM

Fall BOM.xlsx

## **Purchasing Plan**

D	Owner the New deed	B b O	0	11-14 D-1(\$)	T-4-1D:(\$)	Tatal Disa Cala Disa at (V/N)	1 1	Notes
Part	Quantity Needed	Purchase Quantity	Current Quanitiy	Unit Price(\$)	Total Price(\$)	Total Price Order Placed (Y/N)	Link https://www.homedepot.com/p/OSB-7-	Notes
		_					16-Application-as-4ft-X-8-ft-	
Plywood	15	5	10	14.98	224.7	Υ	Sheathing-Panel-386081/202106230 https://www.homedepot.com/p/2-in-x-3	
							in-x-8-ft-2-Select-Grade-Dimensional-	
							Lumber-	
Wood Beams	35	15	20	2.98	104.3	Y	845000/100038668?MERCH=REC	
#8 2in Flat head Philips exterior screws(5lb pk of							https://www.homedepot.com/p/Grip- Bite-8-x-2-in-2-Phillips-Bugle-Head- Coarse-Thread-Coated-Exterior-Wood-	
6720	1	0	1	33.39	33.39	Υ	Screws-5-lb-Box-PTN2S5/100136822	
2" Corner Brace Zinc 3X 20pk	3	0	3	14.97	44.91	Υ	https://www.homedepot.com/p/Everbilt- 2-in-Zinc-Plated-Corner-Brace-20- Pack-40915/326115906	
#6 3/4in Flat Head Philips metal to wood screws (50 pk)	4	0	4	5.98	23.92	Y	https://www.homedepot.com/p/DECKM ATE-Marine-Grade-Stainless-Steel-6- X-3-4-in-Flat-Head-Phillips-Screw-50- Pieces-866900/319949363	
Waterproof floor putty	1	0	1	6.97	6.97	Y	https://www.homedepot.com/p/ROBERT S-Palette-Quick-Repair-Putty-3-oz- Tan-for-Wood-Laminate-and-Vinyl- Flooring-PC7730/204846143	Used to seal any mistakes
5" x 5" Zinc T-Plate	12	0	12	2.86	34.39	Υ	https://www.homedepot.com/p/Everbilt- 5-in-x-5-in-Zinc-Plated-T-Plate-6- Pack-12504/315016295	
Insulation	2	0	2	20.67	41.34	Y	https://www.homedepot.com/p/Grip- Bite-8-x-2-in-2-Phillips-Bugle-Head- Coarse-Thread-Coated-Exterior-Wood- Screws-5-lb-Box-PTN2S5/100136822	No longer being used but already purchased
Reptile Humidity & Thermometer	2	0	2	6.99	13.98	Y	https://www.petsmart.com/reptilerenvironmental-control-and-lighting/humidity-and-temperature-control/zoo-med-creatures-dual-thermometer-and-humidity-gauge-49700.html?gclid=093bdda5d9a41bbfa	Used in last semesters prototype
Digital Water Thermometer	2	0	2	11.99	23.98	Υ	https://www.petsmart.com/fish/heating- and-lighting/heating-and-lighting- accessories/top-fin-digital-aquarium- thermometer-16591.html	Used in last semesters prototype
Plastic Water Container	3	0	3	4	12	Υ	https://www.target.com/p/12-34-x-6-34-x-4-34-all-purpose-storage-1-2-storage-bin-brightroom-8482/-/A-83279865#lnk=sametab	Used in last semesters prototype
Hot Glue Sticks	2	0	2	3	6	Y	https://www.michaels.com/product/4- full-size-dual-temperature-glue-sticks- by-ashland- 10228078?michaelsStore=9608&inv=15	Used in last semesters

**NORTHERN ARIZONA UNIVERSITY** 


## **Purchasing Plan**

1500W Water Heater							https://www.priidea.com/products/15000w- titanium-portable-hot-tub-heater-briidea-	
1000M Mater Heater	1	1	0	104.5	104.5	Υ	fully-immersion-water-heater-with-anti-	
LED Detachable							https://www.homedepot.com/p/Husky-800	
Tripod Light	_	_	_				Lumen-LED-Rechargeable-Detachable-	
mpod Light	2	0	2	24.88	49.76	Υ	Tripod-Work-Light-K40526/331757756 https://www.homedepot.com/p/UAP-	
							Touch-N-Foam-Wall-and-Cavitu-Low-	
Wall & Cavity Foam							GWP-10-5-lb-Sprau-Foam-Sealant-Kit-	
	1	0	1	199.98	199.98	Υ	7565000351/325778090	
Wide Spray Foam Sealant							https://www.homedepot.com/p/GREAT-	
				00.00	450.00		STUFF-Wide-Spray-18-oz-Spray-Foam-	
	4	0	4	39.98	159.92	Υ	Sealant-12107825/334627354	
Arduino	1	0	1	0	0	Υ	https://www.arduino.cc/	
							Wave-48-in-x-54-in-D-Round-12-ft-Blue-	
							Standard-Gauge-Overlap-Liner-NL321- 20/320489524?MERCH=REC	
Vinyl Pool liner							ry cart rrn/a0n/an/an/a	
	1	1	0	104.97	104.97	Υ	n/an/a	
Hinges	7	0	0	0		N		
1 miges	,	0	0				https://www.homedepot.com/p/DAP-Alex-	
Silicone Caulk							Plus-10-1-oz-White-Acrulic-Latex-Caulk-	
	2	2	0	6.89	13.78	Y	Plus-Silicone-18103/100097524	
							https://www.homedepot.com/p/Husky-10-	
Caulk Gun	_		_	44.00	44.00		oz-Heavy-Duty-High-Leverage-Drip-Free-	
	1	1	0	11.98	11.98	N	Caulk-Gun-19PT0902/314993814 https://www.nomedepot.com/pr/3IVI-8511-	
Construction Mask							N95-Sanding-and-Fiberglass-Disposable-	
Construction mask	6	6	0	2	12	Y	Respirator-with-Cool-Flow-Valve-1-Pack-	For Safety
							https://www.uline.com/Product/Detail/s- 23309-L/Nitrile-Gloves/Uline-Black-	
4mm Rubber Gloves							Industrial-Nitrile-Gloves-Powder-Free-4-	
(200 count)							Mil-	
	2	2	0	13	26	Υ	Large?pricode=WB1029&gadtype=pla&id=	For Safety
							https://www.homedepot.com/p/Commerci	
							al-Electric-1-Gang-Extra-Duty-Horizontal-	
CGFI Outlit box							Vertical-Non-Metallic-Weatherproof-In- Use-Cover-16-in-1-Configurations-Clear-	
	3	3	0	10.48	31.44	Υ	WCW1PC/300849073	
		-	0	10.40	01.44		<u> </u>	
Desicoant	1	0	0	0		N		Undecided
+	1	0	U	0		IN		Oridecided
Glass Siphon								
Receiving Dish	1	0	0	0		N		Undecided
Scientific Balance	1	0	0	0		N		Undecided
Scientific balance	1	U	U	U		IN		Undecided
Rubber Siphon Tube								
	1	0	0	0		N		Undecided
							https://www.homedepot.com/pep/Leviton-	
GCFI Outlit							20-Amp-Self-Test-SmartlockPro-Slim-	
22.72	3	3	0	15.51	46.53	٧	GFCI-Duplex-Outlet-White-3-Pack- GFNT2-3W-M22-GFNT2-03W/205999893	
	J	J					GI 1412-5W-14122-GI 1412-05W1200333633	
				Total Cost (\$):	1330.74	· · · · · · · · · · · · · · · · · · ·		
			OTUEE					

# Manufacturing Plan

Part	Time [hours]	Manufacturing Method	Progress Percentage
Apparatus Base, Walls, & Roof	15.5	Woodworking/Assembly	85%
Data Collection Circuit	3	Electronics/Wiring	50%
Water Pool	2.5	Woodworking/Lining	20%
Air Cooling System	3	Installation/Mounting	20%
Sensor Mounting and Calibration	2	Calibration	35%
Siphon for Water Level & Balance Calibration	1.5	Tubing/Calibration	0%
Total	27.5		35.0%


### **Demonstration**





NORTHERN ARIZONA UNIVERSITY Brendan Steele, 9/22/25, SRP EVAP

### **Demonstration**



#### **SHT21**

- $\pm 0.3 0.4$  °C
- $\pm 2 3 RH$
- Factory Calibrated

#### DHT11

- ± 2°C
- ± 5 RH
- Factory Calibrated

#### DS18B20 x 2

- ±5 °C
- Factory Calibrated

#### **Thermistor**

- ± 1 - 2°C

**Not Calibrated** 

### **Gantt Chart**

Link to Gantt Chart

SRP EVAP Gantt Chart ME486C.xlsx

# Thank You!